

ISE CSN (Centro di Supporto Nazionale)	DOCUMENTO TECNICO		RIFERIMENTI	
	200402APN02	CONFIGURAZIONI GPRS OPERATORI MOBILI ITALIANI		26/04/04
	REDATTO	CONTROLLO	AUTORIZZAZIONE	REPARTO
	Filippo NATOLI		Giuseppe PITTARI	CSN

DIAL UP CONFIGURATION FOR GPRS NETWORK PARAMETERS Network WIND			
WIRELESS MODULES GPRS 900/1800 MHz			
		Windows Configuration	
Reference	Description	WIN. 95-98	WIN. 2.000
Phone Number (Dial)	Mandatory	*99***1#	*99***1#
User Name	Mandatory	NONE	NONE
Password	Mandatory	NONE	NONE
APN Name (complete string)	Modem Extra setting	at+cgdcont=1,"IP","internet .wind"	at+cgdcont=1,"IP"," internet.wind"
Primary DNS	Dial Up(TCP/IP)-DNS Server address	Obtain DNS Server address automatically	Obtain Server address automatically
Radius Protocol used	Security (Customer Setting)	Tipycal (recommended setting)	(PAP);(SPAP);(CHAP) three flags
Internet Web Browsing	Address of Proxy	Direct Connection	Direct Connection

ISE CSN (Centro di Supporto Nazionale)	DOCUMENTO TECNICO		RIFERIMENTI	
	200402APN02	CONFIGURAZIONI GPRS OPERATORI MOBILI ITALIANI		26/04/04
	REDATTO	CONTROLLO	AUTORIZZAZIONE	REPARTO
	Filippo NATOLI		Giuseppe PITTARI	CSN

Hyper Terminal commands			
COMMAND	EFFECT	RESULTS	NOTE
at	check the connection between phone and PC	OK	
at+cgatt?	verify the GPRS attach procedure	0=no attach 1=attach	
at+cgatt=1	force the GPRS attach	OK	
at+cgatt=0	force the GPRS detach	OK	
NOTE: Close hyper terminal window after command insertion			